

## **Declaration of Performance**

### No. SEWPVARDOP 04

## LVL by Stora Enso, T grade

#### 1. Construction product

Structural laminated veneer lumber which fulfills the requirements according to EN 14374:2004. For further or more detailed information on the delivered product, in addition to what to what is given below, see information on the packaging or in possible accompanying commercial document.

#### 2. Type

LVL by Stora Enso, T grade. Dimensions: Thickness 27-75 mm, Width 45-2500 mm

#### 3. Intended use of the construction product

Buildings and bridges.

#### 4. Producer

Company:

Stora Enso Wood Products Oyj, Varkaus LVL mill

Address:

Taipaleentie 15

78201 Varkaus

Finland

Telephone:

+358 2046 111

E-mail:

jaakko.huovinen@storaenso.com

Web site:

www.storaenso.com

# 5. System of assessment and verification of constancy of performance of the construction product System 1

#### 6. Certification

The notified body Inspecta Sertificinti Oy (identification number 0416) has performed an initial inspection of the manufacturing plant and of the factory production control and performs continuous surveillance, assessment and evaluation of our factory production control. Inspecta Sertificinti Oy has issued CE Certificate of constancy of performance 0416-CPR-13110-01.

#### 7. Declared performance

Performance for LVL in conformity with the harmonized European standard EN 14374:2004 Timber Structures – Structural laminated veneer lumber – Requirements.

Property	Performance	×
Thickness	27–75 mm	
Strength		
Bending strength		1
Edgewise (depth 300mm)	27,0 N/mm <sup>2</sup>	
Size effect parameter	0,15	
Flatwise	32,0 N/mm <sup>2</sup>	
Tension strength,	24 N/mm <sup>2</sup>	
Parallel to grain (length 3000mm)		EN 14374:2004
Compression strength, Parallel to grain	26 N/mm <sup>2</sup>	
Shear strength, edgewise parallel to	3,6 N/mm <sup>2</sup>	
grain	D	
Modulus of elasticity		
Parallel to grain, along, mean	10 000	
Parallel to grain, along, 5 % -fractile	N/mm <sup>2</sup>	
	8 800 N/mm <sup>2</sup>	
Density		
Mean	440 kg/m <sup>3</sup>	
5 % - fractile	410 kg/m <sup>3</sup>	
Reaction to fire	D-s1, d0	
Release of formaldehyde	E1	
Natural durability against biological attack	4	

8. The performance for our construction product LVL by Stora Enso, T grade is in accordance with the declared performance given in point 7. The manufacturer mentioned in point 4 is solely responsible for this declaration of performance.

Varkaus 31.01.2022

Jaakko Huovinen Operations Director Stora Enso Oyj, Wood Products Varkaus Unit