



March 2008

## EnviPress

**EnviPress** stands for standard setting quality. Best print results with high opacity.

### End uses

retail promotions  
newspaper inserts  
TV guides  
mass circulation magazines  
catalogues  
mail order  
supplements  
gift-wrapping

### Product description

SC-B super-calendered uncoated mechanical paper

### Printing method

heatset web offset

### Producer

Dawang Mill

## Technical specifications

|  |                    |           |           |           |           |           |           |
|--|--------------------|-----------|-----------|-----------|-----------|-----------|-----------|
| <b>Grammage</b><br>ISO 536               | g/m <sup>2</sup>   | <b>45</b> | <b>48</b> | <b>52</b> | <b>56</b> | <b>60</b> | <b>64</b> |
| <b>D65-Brightness</b><br>(D 65/10°)      | %                  | 66        | 66        | 66        | 66        | 66        | 66        |
| <b>Opacity</b><br>ISO 2471               | %                  | 91        | 93        | 94        | 95        | 96        | 96        |
| <b>Gloss</b> Hunter,<br>ISO 8254-1       | %                  | 30        | 30        | 30        | 30        | 30        | 30        |
| <b>Roughness</b> PPS 1MPa,<br>ISO 8791-4 | µm                 | 1.65      | 1.65      | 1.65      | 1.65      | 1.65      | 1.65      |
| <b>Bulk</b><br>ISO 534                   | cm <sup>3</sup> /g | 0.90      | 0.90      | 0.90      | 0.90      | 0.90      | 0.90      |
| <b>Thickness</b><br>ISO 534              | µm                 | 42        | 46        | 50        | 52        | 55        | 59        |

## Reel specifications

|               |           |
|---------------|-----------|
| trimmed width | 689 cm    |
| core          | 76/152 mm |
| max. width    | 320 cm    |
| min. width    | 50 cm     |
| max. diameter | 130 cm    |
| min. diameter | 80 cm     |
| max. weight   | 3500 kg   |

## Wrapping

polyethylene laminated kraft paper

## Environment

100% recovered fibre content  
renewable fibre  
recyclable paper  
recyclable packaging materials