



January 2012

## EnviPress

EnviPress stands for standard setting quality. Best print results with high opacity.

## HSWO

retail promotions  
newspaper inserts  
TV guides  
mass circulation magazines  
catalogues  
mail order  
supplements  
gift-wrapping

## Product description

SC Prime super-calendered  
uncoated mechanical paper

## Printing method

heatset web offset

## Producer

Dawang Mill

## Technical specifications

		42	45	48	52	56	60	64	70
<b>Grammage</b> ISO 536	g/m <sup>2</sup>	42	45	48	52	56	60	64	70
<b>D65-Brightness</b> D 65/10°	%	66	66	66	66	67	67	67	67
<b>CIE Whiteness</b> ISO 11476, C/2°	%	66	66	66	66	66	66	66	66
<b>Y-value</b> ISO 2476, C/2°	%	64	64	64	64	65	65	65	65
<b>Opacity</b> ISO 2471	%	91	92	93	94	95	96	97	98
<b>Gloss</b> Hunter, ISO 8254-1	%	32	32	32	32	32	32	32	32
<b>Smoothness</b> PPS 1MPa, ISO 8791-4	µm	1.65	1.65	1.65	1.65	1.65	1.65	1.65	1.65
<b>Bulk</b> ISO 534	cm <sup>3</sup> /g	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
<b>Thickness</b> ISO 534	µm	39	42	45	48	52	56	59	65

## Reel specifications

trimmed width	679 cm
core	76/152 mm
max. width	320 cm
min. width	50 cm
max. diameter	150 cm
min. diameter	80 cm
max. weight	3500 kg

## Wrapping

polyethylene laminated  
kraft paper

## Environment

renewable fibre  
recyclable paper  
recyclable packaging materials