

January 2012

ExoPress 68, 72, 76

ExoPress papers have first-class printability and runnability together with overall cost-efficiency. The range includes ExoPress 64, 68, 72, 76, 80 for CSWO printing and ExoPress 60, 68, 72, 76 for HSWO and Rotogravure printing.

CSWO

End uses
inserts
supplements
advertisements
magazines
special newspapers
free sheets
books

Product description

MF machine finished uncoated mechanical paper

Printing method

coldset web offset

Producer

Kvarnsveden Mill

Technical specifications

		45	49	52	55	60
Grammage ISO 536	g/m ²	45	49	52	55	60
D65-Brightness D 65/10°	%	68/72	68/72	68/72/76	68/72/76	76
CIE Whiteness ISO 11476, C/2°	%	58/61	58/61	58/61/79	58/61/79	79
Opacity ISO 2471	%	88-92	90-93	90-92	91-93	92-95
Smoothness Bendtsen, ISO 8791-2	ml/min	100	100	100	100	100
Bulk ISO 534	cm ³ /g	1.6	1.6	1.6	1.6	1.6
Thickness ISO 534	µm	72	77	82	87	92

Reel specifications

trimmed width
core
max. width
max. diameter
min. diameter

Kvarnsveden

840/868 cm
76/150 mm
432/310 cm
125 cm
100 cm

Wrapping

polyethylene laminated kraft paper

Environment

renewable fibre
recyclable paper
recyclable packaging materials