

January 2012

TerraPress

High-bright LWC for highest demands in printability. Excellent printed gloss and opacity.

Rotogravure

End uses
 high print run superior magazines
 travel brochures
 catalogues

Product description
 LWC slightly mechanical coated paper

Finish
 gloss

Printing method
 rotogravure

Producer
 Corbehem Mill
 Kabel Mill (wide reels >363 cm)

Technical specifications

	g/m ²	57	60	65	70
Grammage ISO 536					
D65-Brightness D 65/10°	%	82	82	85	85
CIE Whiteness ISO 11476, C/2°	%	84	84	88	88
Opacity ISO 2471	%	89.0	90.5	91.0	92.5
Gloss Hunter ISO 8254-1	%	60	62	63	65
Smoothness PPS 1MPa, ISO 8791-4	µm	0.7	0.7	0.7	0.7
Bulk ISO 534	cm ³ /g	0.8	0.8	0.8	0.8
Thickness ISO 534	µm	46	48	52	55

Reel specifications

trimmed width
 core
 max. width
 min. width
 max. diameter
 min. diameter
 max. weight

Corbehem

860 cm
 76/150 mm
 363 cm
 44 cm
 125 cm
 100 cm
 6000 kg

Kabel

720 cm
 76/150 mm
 432 cm
 38.8 cm
 130 cm
 100 cm
 10000 kg

Wrapping

test and kraft liner
 polyethylene

Environment

renewable fibre
 recyclable paper
 recyclable packaging materials