HOLZ FORSCHUNG AUSTRIA

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

CLT – Cross Laminated Timber

according to the product specification listed in the current addendum to this certificate placed on the market by

Company

STORA ENSO WOOD PRODUCTS GMBH

Brand 44
AT-3531 Brand

and produced in the manufacturing plant

Stora Enso Wood Products GmbH
Bahnhofstraße 31
AT-3370 Ybbs

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

ETA-14/0349, issued on 13.04.2026
and
EAD 130005-00-0304

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0892
Date of first issue: 01.10.2015
Date of issuance: 21.07.2026

This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforschung.at.

Akkreditierung Austria A 0923 ISO/IEC 17065

Dr. Andreas Neumüller
Authorised signatory

PD Gerhard Grüll
Head of the Certification Body

HOLZFORSCHUNG AUSTRIA - ÖSTERREICHISCHE GESELLSCHAFT FÜR HOLZFORSCHUNG ZVR 850936522
A-1030 Wien, Franz-Grill-Straße 7 Tel +43-1/798 26 23-0 Fax +43-1/798 26 23-50
hfa@holzforschung.at www.holzforschung.at

HOLZ FORSCHUNG AUSTRIA

Addendum to certificate 1359-CPR-0892

Date of issuance: 21.07.2026

Scope of certification for the following products:

CLT – Cross laminated timber

Solid wood slabs to be used as structural elements in building

Structure:	minimum 3-layers, up to 20 layers, layers arranged perpendicular (angle of 90°), standard construction with 3, 5 and 7 layers
Strength classes of the laminations:	C24 / T14 according to EN 338
Type of laminations:	Boards
Element thickness:	42 - 350 mm
Element size (w x l):	max. 3,5 x 16,5 m
Service classes:	1, 2
Timber species:	PCAB – spruce/ ABAL – fir; PNSY – pine
Adhesive:	
- Finger joints	Type I: PUR according to EN 15425
- Edge bonding boards	EPI: non-load bearing
- Face bonding	Type I: PUR according to EN 15425