

# BergaJet N

by Stora Enso



**BergaJet N** is a woodfree uncoated paper designed for use in pigment ink and dye based production inkjet printers.

- Excellent multicolour print reproduction
- Good runnability in printing and post-printing processes

## PRODUCER

Nymölla Mill

## TYPICAL END USES

Transpromos  
Statements  
Direct mail  
Books  
Manuals  
Catalogues

## PRINTING METHODS

Inkjet printing

## CONVERTING

Reel-to-A4  
Reel-to-reel  
Reel-to-fanfold

## POST PRINTING PROCESS

Automatic inserting  
Cutting and folding  
Collating  
MICR

## ICC-PROFILE

Download: [Technical Resource Centre](#)

## TECHNICAL SPECIFICATIONS (target values after production)

Substance		g/m <sup>2</sup>	75	80	90	100
Brightness	ISO 2470-2 (C/2°)	%	98	98	98	98
CIE Whiteness	ISO 11475 (D65/10°)	%	161	161	161	161
Opacity	ISO 2471 (C/2°)	%	92	94	96	96
Bulk	ISO 534	cm <sup>3</sup> /g	1.30	1.30	1.30	1.30
Roughness	Bendtsen, ISO 8791-2	ml/min	240	240	240	240
Moisture	ISO 287	%	5.5	5.5	5.5	5.5
Ageing resistance	ISO 9706		yes	yes	yes	yes

## REEL SPECIFICATIONS

Cores: 70 mm and 76 mm  
Diameters: min. 1000 mm, max. 1200 mm  
Width: min. 210 mm, max. 2600 mm

## ENVIRONMENT

Renewable fibre  
Recyclable paper  
Recyclable packaging materials

## CERTIFICATES

EU Ecolabel SE/011/001  
Nordic Ecolabel 3044 0044  
Environment ISO 14001  
Quality ISO 9001  
Energy ISO 50001  
Health and Safety ISO 45001  
FSC® CoC, license code FSC® C015932  
PEFC™ CoC, license code PEFC/02-31-86  
For more information:  
[Paper Sustainability](#)

## STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.

OFFICE USE: Reel Fed Inkjet

Updated: september 2021