

# BergaJet

by Stora Enso



BergaJet is a woodfree uncoated paper designed for high-speed inkjet web presses using pigmented inks or dye inks.

- Excellent multicolour print reproduction
- Good runnability in printing and post-printing processes
- Laser guaranteed and suitable for OCR and offset printing

## TYPICAL END USES

Transpromos  
Statements  
Direct mail  
Books  
Manuals  
Catalogues  
Plotter printouts

## PRINTING METHODS

Inkjet

## CONVERTING

Reel-to-A4  
Reel-to-reel  
Reel-to-fanfold

## POST PRINTING PROCESS

Automatic inserting  
Cutting and folding  
Collating  
OCR  
MICR

## PRODUCER

Veitsiluoto Mill

L* a* b* target values	L*	a*	b*	Fluorescence (ISO 12647-2)
ISO 5631-3 (D50/2°)	93	2.8	-10.8	High

## TECHNICAL SPECIFICATIONS (target values)

Substance		g/m <sup>2</sup>	75	80	90	100	115
Brightness	ISO 2470-2 (D65/10°)	%	109	109	109	109	109
CIE Whiteness	ISO 11475 (D65/10°)	%	163	163	163	163	163
Opacity	ISO 2471 (D65/10°)	%	92	95	96	97	98
Bulk	ISO 534	cm <sup>3</sup> /g	1.30	1.30	1.30	1.30	1.30
Roughness	Bendtsen, ISO 8791-2	ml/min	270	270	270	270	270
Moisture	ISO 287	%	5.5	5.5	5.5	5.5	5.5

## REEL SPECIFICATIONS

Cores: 70 mm and 76 mm  
Diameters: min. 1000 mm, max. 1200 mm  
Width: min. 210 mm, max. 2600 mm

## CERTIFICATES

EU Ecolabel FI/011/007  
Nordic Ecolabel 4044 0001  
ISO 9706  
ISO 14001  
ISO 9001  
ISO 50001  
OHSAS 18001  
FSC® CoC, license code FSC® C015932  
PEFC™ CoC, licence code PEFC/02-31-86

## ENVIRONMENT

Renewable fibre  
Recyclable paper  
Recyclable packaging materials

## STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.

OFFICE USE: Reel Fed Inkjet

Updated: 30 July 2019