



Bulky is an uncoated mechanical book paper grade for especially high volume print runs.

- Available in many options of bulk
- High runnability

PRODUCER

Anjala Mill

TYPICAL END USES

Hard and soft cover books Paperbacks Text books Children's books School books Puzzle books

PRINTING METHODS

CSWO HSWO SFO Digital

SHADE Creamy

L* a* b* values	L*	a*	b*
ISO 5631-2 (D65/10°)	87.2	-1.5	9.0

TECHNICAL SPECIFICATIONS (target values)

Substance		g/m²	50	53
Bulk	ISO 534	cm³/g	2.3	2.3
Thickness	Tappi T411	μm	115	122
Brightness	ISO 2470-2 (D65/10°)	%	62	62
Opacity	ISO 2471	%	93	94

REEL SPECIFICATIONS

Core: 76 mm

Trimmed width: 5400 mm Width: min. 300 mm, max. 2500 mm

Diameters: min. 1000 mm, max. 1250 mm

Max. weight: 3000 kg

CERTIFICATES

EU Ecolabel FI/011/002 Quality ISO 9001 Environment ISO 14001 Health & Safety ISO 45001 Energy ISO 50001 FSC®-CoC (FSC®-C127282) *

FSC® -CoC (FSC® -C127282) ^ PEFC -CoC (PEFC/02-31-247) *

* FSC and PEFC certified paper available upon request For more information:

www.storaenso.com/download-centre

ENVIRONMENT

Renewable fibre Recyclable paper Recyclable packaging materials

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.