

EnviMatt

by Stora Enso



EnviMatt is a soft calendered uncoated mechanical paper.
It is made out of 100% recycled fibre.

- High Bulk
- High Print Sharpness
- High Opacity

PRODUCER

Langerbrugge Mill

TYPICAL END USES

Magazines
Read Magazines
Inserts
Supplements

PRINTING METHODS

HSWO
InkJet
Waterless Printing

L* a* b* target values	L*	a*	b*	Flourescence (ISO 12647-2)
ISO 5631-3 (D50/2°)	88	-0.8	2.5	Faint

TECHNICAL SPECIFICATIONS (target values)

Substance		g/m ²	49	52	56	60
Brightness	ISO 2470-2	%	72	72	72	72
Opacity	ISO 2471	%	95	96	97	97
Gloss Hunter	ISO 8254-1	%	8	8	8	8
Bulk	ISO 534	cm ³ /g	1.25	1.25	1.25	1.25
Smoothness	ISO 8791-4 PPS (1MPa)	µm	4	4	4	4

REEL SPECIFICATIONS

Cores: 76 mm, 150 mm
Trimmed width: 5720 mm
Width: min. 360 mm, max. 2680 mm
Diameters: min. 1000 mm, max. 1500 mm
Max. weight: 7700 kg

CERTIFICATES

EU Ecolabel FI/011/007
Quality ISO 9001
Environment ISO 14001
Health & Safety ISO 45001
Energy ISO 50001
[FSC®CoC \(FSC®C015932\)](#)
[PEFC™ CoC \(PEFC/02-31-86\)](#)
For more information:
www.storaenso.com/paper-sustainability

ENVIRONMENT

Renewable fibre
Recyclable paper

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.