

Exo 68

by Stora Enso



Exo is a machine finished uncoated mechanical newsprint speciality.

- First class printability and runnability
- Overall cost efficiency

PRODUCER

Kvarnsveden Mill

TYPICAL END USES

Inserts
Supplements
Advertisements
Magazines
Special Newspapers
Free sheets

PRINTING METHODS

CSWO

ICC-PROFILE

Download:

<https://info.storaenso.com/paper-resource-centre-prepress>

CHARACTERIZATION DATA

FOGRA 42

L* a* b* target values	L*	a*	b*	Fluorescence (ISO 12647-2)
ISO 5631-3 (D50/2°)	86	0.4	1.8	Faint

TECHNICAL SPECIFICATIONS (target values)

Substance		g/m ²	52
Brightness	ISO 2470-2 (D65/10°)	%	68
CIE Whiteness	ISO 11476 (C/2°)	%	57
Opacity	ISO 2471	%	94
Thickness	ISO 534	µm	86
Bulk	ISO 534	cm ³ /g	1.6
Smoothness	ISO 8791-4 PPS (1MPa)	µm	3.6

REEL SPECIFICATIONS

Core: 76 mm, 150 mm
Trimmed width: 8220 mm
Width: max. 4320 mm
Diameters: 1250 mm

CERTIFICATES

EU Ecolabel FI/011/007
Quality ISO 9001
Environment ISO 14001
Health & Safety ISO 45001
Energy ISO 50001
[FSC®CoC \(FSC®C015932\)](#)
[PEFC™ CoC \(PEFC/02-31-86\)](#)
For more information:
www.storaenso.com/paper-sustainability

ENVIRONMENT

Renewable fibre
Recyclable paper
Recyclable packaging materials

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.