

# Novobase

by Stora Enso



Novobase is a single layer mechanical wallpaper base.

**PRODUCER**  
Anjala Mill

**TYPICAL END USES**  
Wall coverings

**CONVERTING METHODS**  
All PVC coating methods

L* a* b* values	L*	a*	b*
ISO 5631-3 (D50/2°)	88.3	0.9	7.5

## TECHNICAL SPECIFICATIONS (target values)

Substance		g/m <sup>2</sup>	80	90	100
Bulk		cm <sup>3</sup> /g	1.8	1.8	1.8
Thickness	ISO 534	µm	144	162	180
Brightness	ISO 2470-2 (D65/10°)	%	64	64	64
Cobb 60	ISO 535	g/m <sup>2</sup>	17	17	17
Wet expansion cd	Mod. ISO 5635	%	1.5	1.5	1.5

## REEL SPECIFICATIONS

Core: 71 mm, 76 mm  
Trimmed width: 8550 mm  
Width: min. 300 mm, max. 2500 mm  
Diameters: min. 1000 mm, max. 1250 mm  
Max. weight: 3000 kg

## CERTIFICATES

Quality ISO 9001  
Environment ISO 14001  
Health & Safety ISO 45001  
Energy ISO 50001  
[FSC® CoC \(FSC® C015932\)](#) \*  
[PEFC™ CoC \(PEFC/02-31-86\)](#) \*  
(\* FSC or PEFC paper is only delivered on customer request.)  
For more information:  
[www.storaenso.com/paper-sustainability](http://www.storaenso.com/paper-sustainability)

## ENVIRONMENT

Renewable fibre  
Recyclable paper  
Recyclable packaging materials

## STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.