

Novobase

by Stora Enso



Novobase is a single layer mechanical wallpaper base.

PRODUCER
Anjala Mill

TYPICAL END USES
Wall coverings

CONVERTING METHODS
All PVC coating methods

L* a* b* values	L*	a*	b*
ISO 5631-2 (D65/10°)	88.0	-0.8	8.1

TECHNICAL SPECIFICATIONS (target values)

Substance		g/m ²	90
Bulk		cm ³ /g	1.8
Thickness	Tappi T411	µm	162
Brightness	ISO 2470-2 (D65/10°)	%	64
Cobb 60	ISO 535	g/m ²	17
Wet expansion cd	Mod. ISO 5635	%	1.5

REEL SPECIFICATIONS

Core: 71 mm, 76 mm
Trimmed width: 5400 mm
Width: min. 300 mm, max. 2500 mm
Diameters: 1000 mm, 1200 mm, 1250 mm
Max. weight: 3000 kg

CERTIFICATES

Quality ISO 9001
Environment ISO 14001
Health & Safety ISO 45001
Energy ISO 50001
FSC® -CoC (FSC® -C127282) *
PEFC -CoC (PEFC/02-31-247) *
* FSC and PEFC certified paper available upon request
For more information:
www.storaenso.com/download-centre

ENVIRONMENT

Renewable fibre
Recyclable paper
Recyclable packaging materials

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.